

# Safety Data Sheet

## According to 91/155 EEC

Printing date 26.07.2007

Revision: 26.07.2007





### 1 Identification of substance:

- **Product details:**
- **Trade name:** **EXTREMULTUS AF cement**
- **Application of the substance / the preparation** Adhesives
- **Manufacturer/Supplier:**  
Forbo Siegling Pty. Ltd.  
Unit 150/45 Gilby Road,  
Mount Waverley Vic 3149  
Ph.: 1300137933  
Fax: 1300137944
- **Information department:**  
Chemical Laboratory  
Email: Claudius.Hayduk@forbo.com  
Siegling GmbH  
30179 Hannover  
Lilienthalstr. 6/8  
Germany Ph: +49 (0) 5116704-0
- **Emergency information:** ++49 (0) 511-6704 0

### 2 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

|                                    |               |  |        |
|------------------------------------|---------------|--|--------|
| CAS: 141-78-6<br>EINECS: 205-500-4 | ethyl acetate |  Xi,  F; R 11-36-66-67 | 25-50% |
| CAS: 78-93-3<br>EINECS: 201-159-0  | butanone      |  Xi,  F; R 11-36-66-67 | 10-25% |

- **Additional information** For the wording of the listed risk phrases refer to section 16.

### 3 Hazards identification

- **Hazard description:**



Xi Irritant  
F Highly flammable

- **Information pertaining to particular dangers for man and environment**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Has a narcotizing effect.

R 11 Highly flammable.

R 36 Irritating to eyes.

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drowsiness and dizziness.

- **Classification system**

The classification was made according to the latest editions of the EU-lists, and expanded upon from company and literature data.

### 4 First aid measures

- **After inhalation** Supply fresh air; consult doctor in case of complaints.
- **After skin contact** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing** If symptoms persist consult doctor.

(Contd. on page 2)

## Safety Data Sheet

### According to 91/155 EEC

Printing date 26.07.2007

Revision: 26.07.2007

Trade name: **EXTREMULTUS AF cement**

· Information for doctor MSDB

(Contd. of page 1)

### 5 Fire fighting measures

- **Suitable extinguishing agents**  
Alcohol resistant foam

CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

- **For safety reasons unsuitable extinguishing agents**

Water.  
Water with full jet.

- **Special hazards caused by the material, its products of combustion or resulting gases:**

In case of fire, the following can be released:

Carbon monoxide (CO)  
Nitrogen oxides (NO<sub>x</sub>)  
Hydrogen cyanide (HCN)  
Hydrogen chloride (HCl)

- **Protective equipment:** Wear self-contained respiratory protective device.

- **Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

### 6 Accidental release measures

- **Person-related safety precautions:**

Keep away from ignition sources  
Ensure adequate ventilation



Wear protective equipment. Keep unprotected persons away.

- **Measures for environmental protection:**

Prevent seepage into sewage system, workpits and cellars.  
Do not allow to enter sewers/ surface or ground water.

- **Measures for cleaning/collecting:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

- **Additional information:** See Section 13 for disposal information.

### 7 Handling and storage

- **Handling**

- **Information for safe handling:**

Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.

- **Information about protection against explosions and fires:**



Keep ignition sources away - Do not smoke.

- **Storage**

- **Requirements to be met by storerooms and receptacles:**

Prevent any seepage into the ground.  
Store in a cool location.

- **Information about storage in one common storage facility:** Store away from foodstuffs.

(Contd. on page 3)

## Safety Data Sheet

### According to 91/155 EEC

Printing date 26.07.2007

Revision: 26.07.2007

Trade name: **EXTREMULTUS AF cement**

(Contd. of page 2)

- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Storage class**  
3A (VCI)  
entzündliche flüssige Stoffe (Flammpunkt bis 55°C)

## 8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Components with limit values that require monitoring at the workplace:**

### 141-78-6 ethyl acetate

|         |  |
|---------|--|
| NES ( ) | Short-term value: 1440 mg/m <sup>3</sup> , 400 ppm<br>Long-term value: 720 mg/m <sup>3</sup> , 200 ppm |
|---------|--|

### 78-93-3 butanone

|         |   |
|---------|---|
| NES ( ) | Short-term value: 890 mg/m <sup>3</sup> , 300 ppm<br>Long-term value: 445 mg/m <sup>3</sup> , 150 ppm |
|---------|---|

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Personal protective equipment**

- **General protective and hygienic measures**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.

- **Breathing equipment:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

Butyl rubber, BR  
Natural rubber, NR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Tightly sealed goggles.

- **Body protection:** Protective work clothing.

## 9 Physical and chemical properties:

- **General Information**

|                |                |
|----------------|----------------|
| <b>Form:</b>   | Fluid          |
| <b>Colour:</b> | Light yellow   |
| <b>Odour:</b>  | Characteristic |

- **Change in condition**

**Melting point/Melting range:** undetermined  
**Boiling point/Boiling range:** 78°C

(Contd. on page 4)

## Safety Data Sheet

### According to 91/155 EEC

Printing date 26.07.2007

Revision: 26.07.2007

Trade name: **EXTREMULTUS AF cement**

(Contd. of page 3)

|  |   |
|--|---|
| · <b>Flash point:</b>                            | -4 °C   |
| · <b>Ignition temperature:</b>                   | 460 °C  |
| · <b>Self igniting:</b>                          | Product is not selfigniting.  |
| · <b>Danger of explosion:</b>                    | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · <b>Explosion limits:</b>                       |   |
| <b>Lower:</b>                                    | 1.8 Vol %   |
| <b>Upper:</b>                                    | 11.5 Vol %  |
| · <b>Vapour pressure at 20 °C:</b>               | 100 hPa   |
| · <b>Density at 20 °C:</b>                       | 0.9 g/cm <sup>3</sup>   |
| · <b>Solubility in / Miscibility with Water:</b> | Not miscible or difficult to mix  |
| · <b>Viscosity:</b>                              |   |
| <b>dynamic at 20 °C:</b>                         | 3000 mPas   |
| · <b>Solvent content:</b>                        |   |
| <b>Organic solvents:</b>                         | 70.0 %  |
| · <b>Solids content:</b>                         | 23.0 %  |

### 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Materials to be avoided:** Reagiert mit starken Oxidationsmitteln
- **Dangerous reactions** No dangerous reactions known
- **Dangerous products of decomposition:** No dangerous decomposition products known

### 11 Toxicological information

- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant

### 12 Ecological information:

- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### 13 Disposal considerations

- **Product:**
- **Recommendation**



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Waste disposal key:** 080409

(Contd. on page 5)

## Safety Data Sheet

### According to 91/155 EEC

Printing date 26.07.2007

Revision: 26.07.2007

Trade name: **EXTREMULTUS AF cement**

(Contd. of page 4)

|                                 |  |
|---------------------------------|--|
| <b>European waste catalogue</b> |  |
| 08 04 09                        | waste adhesives and sealants containing organic solvents or other dangerous substances |

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

- **Recommended cleansing agent:**

Solvent naphtha  
Verdüner 20022

## 14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 3 Flammable liquids.  
Ziffer/Buchstabe: F1
- **Danger code (Kemler):** 33
- **UN-Number:** 1133
- **Packaging group:** II
- **Label:** 3
- **Description of goods:** 1133 ADHESIVES, special provision 640D

- **Maritime transport IMDG:**



- **IMDG Class:** 3
- **UN Number:** 1133
- **Label:** 3
- **Packaging group:** II
- **EMS Number:** F-E,S-D
- **Marine pollutant:** Yes
- **Propper shipping name:** ADHESIVES

- **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1133
- **Label:** 3
- **Packaging group:** II
- **Propper shipping name:** ADHESIVES

## 15 Regulations

|  |               |
|--|---------------|
| <b>Australian Inventory of Chemical Substances</b> |               |
| 141-78-6   | ethyl acetate |
| 78-93-3  | butanone      |

- **Markings according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials

(Contd. on page 6)

## Safety Data Sheet

### According to 91/155 EEC

Printing date 26.07.2007

Revision: 26.07.2007

**Trade name: EXTREMULTUS AF cement**

(Contd. of page 5)

**Code letter and hazard designation of product:**

 Xi Irritant  
 F Highly flammable

**Risk phrases:**

- 11 Highly flammable.
- 36 Irritating to eyes.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

**Safety phrases:**

- 9 Keep container in a well-ventilated place.
- 16 Keep away from sources of ignition - No smoking.
- 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 29 Do not empty into drains.
- 60 This material and its container must be disposed of as hazardous waste.

**National regulations**
**Technical instructions (air):**

| Class | Share in % |
|-------|------------|
| II    | 20.0       |
| NK    | 50.0       |

- **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

### 16 Other information:

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant R-phrases**

- 11 Highly flammable.
- 36 Irritating to eyes.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

**Department issuing MSDS:** Chemical Laboratory

**Contact:**

C.Hayduk  
 Tel.-Nr. +49 511 6704 214  
 Fax-Nr. +49 511 6704 489  
 Mobil-Nr.+49 151 11741970

- **\* Data compared to the previous version altered.**

AUS