

Safety data sheet

According to 91/155 EEC

Printing date 22.11.2010

Version number 14

Revision: 22.11.2010



1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name: LF-Hardener Comp.B**
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the preparation** Quenchant
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Forbo Siegling Pty. Ltd
Factory 1, 124-126 Rodeo Drive
Dandenong South
Victoria 3175. Australia
Ph.: 1300137933
Fax: 1300137944
- **Information department:**
Chemical Laboratory
Email: Claudius.Hayduk@forbo.com
- **Emergency telephone number:**
(001) 352 323 3500 (Transport hazardous materials)
++49 (0) 511-6704-214

2 Composition/information on ingredients

- **Description:** Mixture of the substances listed below with nonhazardous additions.


- **Dangerous components:**

CAS: 141-78-6	ethyl acetate	 Xi R36;  F R11	70-90%
EINECS: 205-500-4		R66-67	


- **Additional information** For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

 Xi; Irritant

R36: Irritating to eyes.

 F; Highly flammable

R11: Highly flammable.

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. Has a narcotizing effect.

- **Classification system:**

The classification was made according to the latest editions of the EU-lists, and expanded upon from company and literature data.

- **Label elements**

- **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials

- **Code letter and hazard designation of product:**



Xi Irritant
F Highly flammable

(Contd. on page 2)

AU

Safety data sheet

According to 91/155 EEC

Printing date 22.11.2010

Version number 14

Revision: 22.11.2010

Trade name: LF-Hardener Comp.B


(Contd. of page 1)

- **Risk phrases:**
 - 11 Highly flammable.
 - 36 Irritating to eyes.
 - 66 Repeated exposure may cause skin dryness or cracking.
 - 67 Vapours may cause drowsiness and dizziness.
- **Safety phrases:**
 - 9 Keep container in a well-ventilated place.
 - 16 Keep away from sources of ignition - No smoking.
 - 23 Do not breathe fumes.
 - 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 - 29 Do not empty into drains.
 - 60 This material and its container must be disposed of as hazardous waste.
- **Special labelling of certain preparations:**
 - Contains isocyanates. See information supplied by the manufacturer
- **Information pertaining to particular dangers for man and environment**
- **Safety phrases:**
 - 9 Keep container in a well-ventilated place.
 - 16 Keep away from sources of ignition - No smoking.
 - 23 Do not breathe fumes.
 - 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 - 29 Do not empty into drains.
 - 60 This material and its container must be disposed of as hazardous waste.
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

4 First aid measures

- **Description of first aid measures**
- **After inhalation** Supply fresh air; consult doctor in case of complaints.
- **After skin contact** Generally the product does not irritate the skin.
- **After eye contact**
 - Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing** If symptoms persist consult doctor.
- **Information for doctor** MSDB

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents**
 - Alcohol resistant foam
- 
 - CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents**
 - Water.
 - Water with full jet.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

 AU
 (Contd. on page 3)

Safety data sheet

According to 91/155 EEC

Printing date 22.11.2010

Version number 14

Revision: 22.11.2010

Trade name: LF-Hardener Comp.B

(Contd. of page 2)

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures



Wear protective equipment. Keep unprotected persons away.

- Environmental precautions:**

Prevent seepage into sewage system, workpits and cellars.
Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

- Reference to other sections**

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling

- Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

- Information about protection against explosions and fires:**



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- Conditions for safe storage, including any incompatibilities**

- Storage**

- Requirements to be met by storerooms and receptacles:** Store in a cool location.

- Information about storage in one common storage facility:** Not required.

- Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls/personal protection

- Additional information about design of technical systems:** No further data; see item 7.

- Control parameters**

- Components with limit values that require monitoring at the workplace:**

141-78-6 ethyl acetate

NES (Australia)	Short-term value: 1440 mg/m ³ , 400 ppm
	Long-term value: 720 mg/m ³ , 200 ppm

- Additional information:** The lists that were valid during the creation were used as basis.

- Exposure controls**

- Personal protective equipment**

- General protective and hygienic measures**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 4)

AU

Safety data sheet

According to 91/155 EEC

Printing date 22.11.2010

Version number 14

Revision: 22.11.2010

Trade name: LF-Hardener Comp.B

(Contd. of page 3)

- **Breathing equipment:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

Natural rubber, NR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Safety glasses

- **Body protection:** Protective work clothing.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Fluid
Colour:	According to product specification
· Odour:	Odourless
· Odour threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range:	Melting point > 120 °C
Boiling point/Boiling range:	76 °C

- **Flash point:** -4 °C

- **Ignition temperature:** 460 °C

- **Decomposition temperature:** Not determined.

- **Self igniting** Not determined.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Explosion limits:**

Lower:	2.1 Vol %
Upper:	11.5 Vol %

- **Vapour pressure at 20 °C:** 100 hPa

· Density at 20 °C:	0.924 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.

- **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix

- **Segregation coefficient (n-octanol/water):** Not determined.

(Contd. on page 5)

Safety data sheet

According to 91/155 EEC

Printing date 22.11.2010

Version number 14

Revision: 22.11.2010

Trade name: LF-Hardener Comp.B

(Contd. of page 4)

- | | |
|----------------------------|--|
| · Viscosity: | |
| dynamic: | Not determined. |
| kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 75.0 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- on the skin:** No irritant effect.
- on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological information

- **Toxicity**
- **Acquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.



Do not allow product to reach ground water, water course or sewage system.

- Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

-AU-

(Contd. on page 6)

Safety data sheet

According to 91/155 EEC

Printing date 22.11.2010

Version number 14

Revision: 22.11.2010

Trade name: LF-Hardener Comp.B

(Contd. of page 5)

13 Disposal considerations

- Waste treatment methods
- Recommendation



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
--

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

- Land transport ADR/RID (cross-border)



- ADR/RID class: 3 Flammable liquids.
- Danger code (Kemler): 33
- UN-Number: 1993
- Packaging group: II
- Label: 3
- UN proper shipping name: 1993 FLAMMABLE LIQUID, N.O.S., special provision 640D (ETHYL ACETATE)
- Tunnel restriction code: D/E

- Maritime transport IMDG:



- IMDG Class: 3
- UN Number: 1993
- Label: 3
- Packaging group: II
- EMS Number: F-E,S-E
- Marine pollutant: No
- Proper shipping name: FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE)

- Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 3
- UN/ID Number: 1993
- Label: 3
- Packaging group: II
- Proper shipping name: FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE)

- Special precautions for user Warning: Flammable liquids.
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

AU

(Contd. on page 7)

Safety data sheet

According to 91/155 EEC

Printing date 22.11.2010

Version number 14

Revision: 22.11.2010

Trade name: LF-Hardener Comp.B

(Contd. of page 6)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture

- Australian Inventory of Chemical Substances

141-78-6	ethyl acetate
26471-62-5	m-tolyldiene diisocyanate

- Standard for the Uniform Scheduling of Drugs and Poisons

None of the ingredients is listed.

- Markings according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials

- Code letter and hazard designation of product:



Xi Irritant
F Highly flammable

- Risk phrases:

11 Highly flammable.
36 Irritating to eyes.
66 Repeated exposure may cause skin dryness or cracking.
67 Vapours may cause drowsiness and dizziness.

- Safety phrases:

9 Keep container in a well-ventilated place.
16 Keep away from sources of ignition - No smoking.
23 Do not breathe fumes.
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
29 Do not empty into drains.
60 This material and its container must be disposed of as hazardous waste.

- Special labelling of certain preparations:

Contains isocyanates. See information supplied by the manufacturer

- National regulations

- Technical instructions (air):

Class	Share in %
NK	75.0

- Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

R11 Highly flammable.
R36 Irritating to eyes.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

- Department issuing MSDS: Chemical Laboratory

- Contact:

C.Hayduk
Tel.-Nr. +49 511 6704 214
Fax-Nr. +49 511 6704 489
Mobil-Nr.+49 151 11741970