

NP 5579
(UU 20U-HC FSTR/FSTR black)



Sketch of cross selection
(not actual size)

Applications

General:

All-purpose folder- and carrier belt for Print-, Paper, Packaging Industries

Postal/Letter sorting special:

- flat sorter
- elastic carrier belt

Advantages

- electrostatic performance of operational and drive face:
HC (highly conductive) class 2, $R_{OA} < 5 \times 10^7 \Omega$, acc. ISO21178
- excellent tracking properties
- consistent tension, no re-tensioning necessary

Technical basic data

Operational-/Drive face	
Coating	Urethane (U)
Texture	Fine texture
Colour	Black
Tension member	Elastisc tension member, 1 ply
Article-no.:	855579
d_{min} (mm)	20
Total thickness (mm)	approx. 1,1
F_w value (N/mm width, $\epsilon=1\%$; $\beta=180^\circ$)	approx. 0,4
Weight (kg/m ²)	approx. 1,2

Product Quick Info 855579 · 12/08
FMS · Reproduction of text or parts thereof only
with our approval.
Modifications reserved.

Forbo Siegling GmbH
Lilienthalstraße 6/8, D-30179 Hannover
Telefon +49 511 67 04 0, Fax +49 511 67 04 305
www.forbo-siegling.com, siegling@forbo.com